


SPIRIT 500



Spirit 500 Pellet


Heating Capacity: 1,500 – 1,800 sq ft.
Overall Efficiency: 85%.
Color: Charcoal.
 Durable Welded Steel Construction
 High Temperature Ceramic Glass
Hopper Capacity: Up to 40 lbs.*
Burn Rate: 0,75 lb. – 4,5 lbs. per hour.
 Thermostat Ready
 Self Ignition
 Two Speed Convection Blower
 Vacuum Safety Switch
 High and Low Switches Protected
 Hopper Switch Protected
 Ash Removal System
 Air Wash System
Emission Rate EPA CERTIFIED: 1.2gr/hr
 Mobile Home Approved (U.S. and Canada)
Optional: Refractive Brick




FRONT VIEW



WALL CLEARANCES



FLOOR PROTECTION



DIMENSIONS

A.- WIDTH: 23.2" (590 mm)
 B.- HEIGHT: 36.5" (926 mm)
 C.- DEPTH: 25.5" (635 mm)

CLEARANCE REQUIREMENTS:

D.- SIDEWALL TO UNIT: 3" (76 mm)
 E.- BACKWALL TO UNIT: 3" (76 mm)
 F.- CORNERWALL TO UNIT: 3" (76 mm)

FLOOR PROTECTION

G.- BACK TO UNIT: 1" (25 mm)
 H.- SIDE TO UNIT: 3" (76 mm)
 I.- FRONT TO UNIT MINIMUM: 6" (152 mm)